

# XL8800 Handfree/ Handheld Laser Barcode Scanner

## Features

---

- u Error rate less than 1/5 million
- u Very comfortable operation sense
- u Service life of button reaches up to 50 million times
- u Supporting the RS232,PS2 and USB interface
- u Full independent intellectual property rights  
(having been award with multiple national patents)
- u Full quakeproof and antiknock design
- u Suiting with each kinds of charge machine



# XL8800 Technical Specifications

## PERFORMANCE PARAMETER

Light Source	Visible Laser Diode 650nm
Scan Pattern	Single Scan
Scan Rate	58 times/second
Scan Precision	0.10mm(pcs0.9)
Scan Width	30mm@scan window, 220mm@200mm
Scan Depth of field	0-250mm(0.33mm. PCS90%)
Decode Capability	EAN-8, EAN-13, UPC-A,UPC-E,Code 39, Code 128, EAN128, Codaber, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Chinese postcode etc.
Corner	30°C
Elevation	60° C
Deflection	55°C
Support Interface	RS232, PS2 and USB
Print Contrast	30% UPC/EAN 100%
Mention Pattern	Buzzer, Indicator
Scan Mode	Manual, auto sense (with stand)

## PHYSICAL PARAMETER

Size	LxWxH: 90mmx70mmx153mm
Weight	128g

## POWER

Voltage	5Volts
Operating Current	85mA
Static Current	36mA
Laser Class	Meet the Grade II National Criteria for Laser Safety
EMC	CE & FCC DOC compliance

## Environmental

Operating Temperature	0° C to 45° C ( 32oF to 104oF)
Storage Temperature	-20° C to 60°
Humidity	5% to 95% relative humidity, non-condensing
Light Levels	4500Lux
Drop	Designed to withstand 1.5m drops

# XL9010

## Wireless Laser Barcode Scanner

### Features

---

- u Full independent intellectual property rights (having been award with multiple national patents).
- u The communication distance on open places is up to 1,200m.
- u Working on 2.4GHzISM frequency.
- u Error rate less than 1/5 million.
- u Service life of button reaches up to 50 million times.
- u Supporting the RS232,PS2 and USB interface.



# XL9010 Technical Specifications

## PERFORMANCE PARAMETER

Light Source	Visible Laser Diode 650nm
Scan Pattern	Single Scan
Scan Rate	58 times/second
Scan Precision	0.10mm(pcs0.9)
Scan Width	30mm@scan window, 220mm@200mm
Scan Depth of field	0-250mm(0.33mm. PCS90%)
Decode Capability	EAN-8, EAN-13, UPC-A,UPC-E,Code 39, Code 128, EAN128, Codaber, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Chinese postcode etc.
Tilt	30°C
Elevation Angle	65°C
Deflection Angle	55°C
Support Interface	RS232, PS2 and USB
Print Contrast	30% UPC/EAN 100%
Mention Pattern	Buzzer, Indicator
Scan Mode	Manual, auto sense (with stand)

## PHYSICAL PARAMETER

Size	LxWxH: 90mmx70mmx153mm
Weight	130g

## POWER

Voltage	5Volts
Operating Current	250mA
Static Current	36mA
Laser Class	Meet the Grade II National Criteria for Laser Safety
EMC	CE & FCC DOC compliance

## ENVIRONMENTAL

Operating Temperature	0° C to 45° C
Storage Temperature	-20° C to 60° C
Humidity	5% to 95% relative humidity, non-condensing
Light Levels	4500Lux
Drop	Designed to with stand 1.5m drops